

Amroy Europe Oy

HYBTONITE Fusion -series

RESIN COMPONENT A

**HYBTONITE®** NANOEPOXY RESIN

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY**

Product name: Name of Substance HYBTONITE® Fusion G2  
 Product type: EPOXY RESIN and fillers

Supplier: Amroy Europe Oy VAT No. FI19869654  
 P. O. Box 144  
 FI – 15101 Lahti, FINLAND www.amroy.fi

Contact numbers/Emergency: Tel. +358 400 815 266  
 Fax. +358 20 711 8609 (production)

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

Preparation description: Blend of liquid epoxy resin(s) and fillers

Dangerous components/constituents

CAS Number:

25068-38-6	Bisfenol A and epichlorohydrin reaction result, epoxy resin	50 – 100 %
	Xi, N; R 36/38, R43, R51/53	
28064-14-4	Bisfenol F epichlorohydrin epoxy resin	0 – 40 %
	Xi, N; R43, R51/53	

**3. HAZARDS IDENTIFICATION**

Xi, N Irritant, toxic to aquatic environment

R36/38 Irritating to eyes and skin.  
 R43 May cause sensitization by skin contact.  
 R51/53 Toxic to aquatic organism. May cause long term adverse effects in the aquatic environment.

**4. FIRST AID MEASURES**

Symptoms and effects: Irritation of the skin and eyes.

First Aid:

- inhalation No specific measures
- skin Do not delay. Remove contaminated clothing. Wash skin with water using soap if available. If persistent irritation occurs, obtain medical attention.
- eye Do not delay. Flush eye with water. If persistent irritation occurs, obtain medical attention immediately.
- ingestion Do not induce vomiting. In the unlikely event of ingestion, obtain medical attention immediately.

Advice to Physicians: If skin sensitisation has developed and a causal relationship has been confirmed, further exposure should not be allowed.

Amroy Europe Oy

HYBTONITE Fusion -series

## 5. FIRE FIGHTING MEASURES

Special hazards:	Not classified as flammable, but will burn. Carbon monoxide may be involved incomplete combustion occurs.
Extinguishing media:	
– small fires	Dry chemical powder, carbondioxide foam, water spray or fog, sand or earth.
– large fires	Foam, water spray or fog.
Unsuitable extinguishing media:	Water in a jet.
Protective equipment:	Full protective clothing and self contained breathing apparatus.
Other information:	Keep adjacent containers cool by spraying with water.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Avoid contact with skin, eyes and clothing
Personal protection:	Wear protective clothing specified for normal operations (see section 8).
Environmental precautions:	Prevent contamination of soil and water. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. If materials enters drains it should be pumped out into a open vessel. Emergence services may need to be called to assist in this operation.
Clean-up methods:	
– small spillage	Absorb or contain liquid with sand, earth or spill control material. Shovel material to labelled sealable container for safe disposal.
– large spillage	Transfer to a labelled container for product recovery or safe disposal. Otherwise treat as for small spillage.

## 7. HANDLING AND STORAGE

Handling:	Avoid contact with skin, eyes and clothing
Storage:	Keep container tightly closed and dry. Palletised loads should be stacked to a maximum of 4 high.
Storage temperatures:	Ambient.

## 8. EXPOSURE CONTROLS / personal protection

Occupational exposure standards:	None established.
Respiratory protection:	Not normally required. In a confined space wear half mask respirator with organic vapour cartridge and build-in particular filter NPF 20 (gas only). If product is applied by spraying wear self contained breathing apparatus.
Hand protection:	Nitrile rubber gloves or butyl rubber gloves, gauntlet type.
Eye protection:	Monogoggles.
Body protection:	Standard issue work clothes, safety boots.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	clear / dark / green / red
Odour:	Slight
Density:	1100 – 1200 kg/m <sup>3</sup> at 25 °C (typical)
Dynamic viscosity:	1.0 – 8.0 Pa·s at 25 °C
Flash point:	Over 200 °C
Solubility in water:	Negligible
N-octanol/ water partition coefficient	Data not available

Amroy Europe Oy

HYBTONITE Fusion -series

## 10. STABILITY / REACTIVITY

Stability:	Stable under normal use conditions. Reacts with strong oxidising agents. Polymerises exothermically with amines, mercaptens and Lewis acids at ambient temperature and above. Polymerises in contact with bases (e.g. caustic soda), ammonia, primary and secondary amines, alcohol's and acids.
Conditions to avoid:	Caustic soda can induce a vaporous polymerisation at temperatures over 150 °C.
Materials to avoid:	Strong oxidising agents. Caustic soda.
Hazardous decomposition products:	Hazardous decomposition products are not expected to form during normal storage.

## 11. TOXICOLOGICAL INFORMATION

Acute toxicity:	
– oral	LD50 > 5000 mg/kg
– dermal	LD50 > 5000 mg/kg
Eye irritation:	Irritant
Skin irritation:	Irritant
Respiratory irritation:	Not irritating
Skin sensitisation:	Skin sensitiser
Carcinogenicity:	A recent review of the available data by the International Agency for Research on Cancer (IARC), has concluded that DGEBA is not classifiable as to its carcinogenicity.
Mutagenicity:	Positive in vitro, but negative in vivo assays.

## 12. ECOLOGICAL INFORMATION

Basis for assessment:	Information given based on data on the components and the ecotoxicology of similar products.
Mobility:	Sinks in water
Persistence/degradability:	Not readily biodegradable
Bioaccumulation:	Has the potential to bioaccumulate
Acute toxicity – fish:	Toxic, 1 < LC50 > 10 mg/l
Sewage treatment:	Toxic, EC50 > 1 – 10 mg/l, to organisms in sewage treatments plants. Toxic to aquatic organisms

## 13. DISPOSAL CONSIDERATIONS

Precautions:	See section 8. Refer to section 7 before handling the product or containers.
Waste disposal:	Recover or recycle if possible. Otherwise incineration or dispose to licensed contractor.
Product disposal:	Drain container thoroughly. Rinse three times with suitable solvent. Treat rinses as for product disposal. After Draining, vent in a safe place away from sparks and re. Send to drum recovered or metal reclaimed.
Local legislation:	Control of Pollution Act 1974. Control of Pollution (Special waste) Regulations 1980. Environmental Protection Act 1990.

## 14. TRANSPORT INFORMATION

Classification / ADR / RID	
Name	Environmentally hazardous liquid substance N.O.S (Epoxy resin)
Classification	9
UN Number	3082
Packaging group	3
Classification	Xi, N

Amroy Europe Oy

HYBTONITE Fusion -series

---

**14. TRANSPORT INFORMATION continued...**

## IMDG / Sea transport

Name	Environmentally hazardous liquid substance N.O.S (Epoxy resin)
Classification	9
UN Number	3082
Packaging group	3
Kemler code	90
Classification	Xi, N

## IATA / Air transport

Name	Environmentally hazardous liquid substance N.O.S (Epoxy resin)
Classification	9
UN Number	3082
Packaging group	3
Classification	Xi, N

---

**15. REGULATORY INFORMATION**

Label name	Epoxy resin (Number average, Molecular weight < 700), Hybtonite Fusion G2
Classification & Labelling:	Irritant. Dangerous for the environment. Xi, N

Risk phrases:	R36/38 Irritating to eyes and skin. R43 May cause sensitisation by skin contact. R51/53 Toxic to aquatic organisms, may cause long-term adverse affects in the aquatic environment.
---------------	---

Safety phrases:	S24 Avoid contact with skin. S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S28 After contact with skin, wash immediately with plenty of soap and water. S37/39 Wear suitable gloves and eye/face protection. S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.
-----------------	--

---

**16. OTHER INFORMATION**

Uses and restrictions:	Compositions for the building and civil engineering industries e.g. flooring compounds, primers, adhesives, mortars, joints and grouts Offshore & Marine applications
------------------------	--

MSDS distribution:	This document contains important information to ensure the safe storage, handling and use of this product. The information in this document should be brought to the attention of the person in your organisation responsible for advising on safety matters.
--------------------	---

---

**DISCLAIMER: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as a guarantee of any specific property of the product.**

---

**Amroy Europe Oy****VAT No: FI19869654**

Postal address

P. O.Box 144, FI – 15101 Lahti, FINLAND

Fax

+358 20 711 8609 (production/orders)

Homepage

www.amroy.fi